

Document Title: Frame and track unit, specifications	Function Group: 700	Information Type: Service Information	Date: 2014/6/25
Profile:			

Frame and track unit, specifications

Specifications

Item		Unit	EC210	EC240
Length of undercarriage		mm	4460	4650
		inch	175.6	183.1
Track link pitch		mm	190	
		inch	7.5	
No. of links		EA	49	51
No. of top roller		EA	2 × 2	2 × 2
No. of bottom roller		EA	9 × 2	9 × 2
Spring	Type	–	Hydraulic adjuster (grease)	
	Spring, set length	mm	444 (17.5)	468 (18.4)
	Spring, free length	(in)	555 (21.9)	570 (22.4)
	Set load	kg (lbs)	13309 ± 800 (29280 ± 1760)	14916 ± 800 (32815 ± 1760)
	Adjust	mm	–20 ~ +100	
		inch	–0.79 ~ +3.94	
Sprocket	No. of tooth	EA	21	21
	Pitch circle diameter	mm	644.6	644.6
		inch	25.3	25.3
No. of shoes		EA	98	102
Ground contact pressure with standard digging unit (boom, arm, and bucket)	600 mm width (Triple grouser)	kgf / cm ²	0.43	0.47
		psi	6.11	6.69
	700 mm width (Triple grouser)	kgf / cm ²	0.38	0.41
		psi	5.40	5.83
	800 mm width (Triple grouser)	kgf / cm ²	0.33	0.36
		psi	4.69	5.12
	900 mm width (Triple grouser)	kgf / cm ²	0.30	0.33
		psi	4.26	4.69
	910 mm width (Swamp)	kgf / cm ²	0.30	0.32
		psi	4.26	4.55

Document Title: Upper (Superstructure), removal	Function Group: 710	Information Type: Service Information	Date: 2014/6/25
Profile:			

Upper frame (Superstructure), removal



WARNING

The superstructure weigh approximate 4 ~ 7 tons (excluding counterweight and digging units). Pay attention to safe footing and the area around the crane before proceeding to remove or install the superstructure.

1. Remove the digging unit.
2. Disconnect turning joint clamping screw, seal cover, hydraulic oil hoses, drain hose, and one servo hydraulic oil hose from turning joint.

NOTE!

Bundle the hoses. Blind plug each disconnected hose and pipe.

3. Remove screws (A) fixing the outer race of the slew ring.




Figure 1
Slew ring installed

- A. Screw
- B. Confirm alignment of match marks

4. Dismantle the cab, counterweight and guard. Place a wire rope on the upper frame and lift it with a crane to an extent that the wire rope is not slack.




Figure 2
Lifting the upper frame

5. Lift the upper frame just a little, and after confirming safety all around, lift it up and out.

Document Title: Upper (Superstructure), installation	Function Group: frame 710	Information Type: Service Information	Date: 2014/6/25
Profile:			

Upper frame (Superstructure), installation

1. Bundle the hoses attached to the turning joint together and place them upright.
2. Coat the screws and threaded holes of the slew ring with "Three bond 1215" (Loctite #515).




Figure 1
Installing the upper frame

3. Lift the upper frame and install it to the slew ring.

NOTE!

Lower the superstructure so that the slew pinion and the slew ring are engaged.

NOTE!

For tightening torque, see torque chart.

NOTE!

Tighten diagonally opposite screws in sequence.

4. Connect the hoses, turning joint clamping screw and seal cover disconnected for removal.

Document Title: Additional counterweight & digging unit	Function Group: 716	Information Type: Service Information	Date: 2014/6/25
Profile:			

Additional counterweight & digging unit

When special digging units (such as : scrap handling clam, log loader etc.,) are installed on the excavators, an additional counterweight is required for stability.

In these cases, check the digging unit specification and compare it carefully to the excavator load lifting capacity chart.

And if in doubt, contact your local dealer for advice.

Additional counterweight can be installed according to special digging units, however we are not responsible for any failure of the excavator or breakage of digging units due to such application.

For reference, an excavator is basically designed only for excavating and is not designed to be used as a crane.

Document Title: Undercarriage, description	Function Group: 7181	Information Type: Service Information	Date: 2014/6/25
Profile:			

Undercarriage, description

Undercarriage consists of idlers, springs, top and botom rollers, sprockets, track links, track frame and track guards.




Figure 1
Structure, undercarriage

1	Track frame	5	Spring package
2	Idler	6	Track guard
3	Top roller	7	Bottom roller
4	Track link	8	Sprocket

Thank you so much for reading.
Please click the “Buy Now!”
button below to download the
complete manual.



After you pay.

You can download the most
perfect and complete manual in
the world immediately.

Our support email:

ebooklibonline@outlook.com